










Kaina nuo 2012.03.01

"Durisol" blokų techniniai duomenys	Mato vnt									
izoliacijos tipas							neoporas	neoporas	su piru	Steico vata
Bloko tipas		DM 15/9	Dsi 30/20	DMi 17/12	DMi 20/13	DMi 25/18	DSs 30/12	DSs 37,5/12	DSs 37,5/12	DSs 37,5/12
Bloko gabaritai: plotis/aukštis/ilgis	cm	15/25/50	30/25/50	17/25/50	20/25/50	25/25/50	30/25/50	37,5/25/50	37,5/25/50	37,5/25/50
Bloko masė	kg/vnt	6	11	9	11	12	10	15	15	15
Putų polistirolo storis	cm						10.5	17.5	17	17.5
Tinkuotos sienos šilumos laidumo koef. U (k)	W/m ² K	1.19	0.641	1.326	1.147	1.067	0.28	0.194	0.142	0.214
Tinkuotos sienos šiluminė varža R	m ² K/W	0.84	1.560	0.753	0.871	0.937	3.569	5.15	7.04	4.672
Tinkuotos sienos garso varža Rw	dB	52	60	55	56	63	48	49	49	49
Statika										
Betono sluoksnio storis	cm	7	20	12	13	18	12	12	12.5	12
Betono plotas	cm ² / m	694	1432	871	958	1334	786	814	825	814
Tinkuotos sienos masė	kg/m ²	275	500	310	354	452	350	380	395	380
Netinkuotos sienos atsparumo ugniai klasė		A2	A2	A2	A2	A2	A2	A2		A2
Blokų poreikis	vnt/m ²	8	8	8	8	8	8	8	8	8
Užpilamo betono poreikis	l/m ²	0.75	155	93	104	143	90	90	0.95	90
Betono armatūros poreikis (orentacinis) *	kg/m ²	2.5	3	3	3	3	3	3	3	3
Darbo laikas be betono paruošimo	min/m ²	45	45	45	45	45	60	60	60	60
Kaina be PVM už vnt	Lt/m ²	5.609	11.26	8.33	8.93	9.84	14.97	18.73		
Kaina be PVM už m ²	Lt/m ²	44.87	90.10	66.65	71.41	78.74	119.72	149.82	sutartinė	sutartinė